(19)





# (11) **EP 3 067 652 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

- (45) Date of publication and mention of the grant of the patent:13.11.2019 Bulletin 2019/46
- (21) Application number: **15461514.0**
- (22) Date of filing: 11.03.2015

## (54) HEAT EXCHANGER AND METHOD FOR EXCHANGING HEAT WÄRMETAUSCHER UND WÄRMETAUSCHVERFAHREN

ÉCHANGEUR DE CHALEUR ET PROCÉDÉ D'ÉCHANGE DE CHALEUR

- (84) Designated Contracting States: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
- (43) Date of publication of application: 14.09.2016 Bulletin 2016/37
- (73) Proprietor: Politechnika Gdanska 80-233 Gdansk (PL)
- (72) Inventors:
  - Wajs, Jan
  - 82-550 Prabuty (PL)
  - Mikielewicz, Dariusz 80-287 Gdansk (PL)

(51) Int Cl.: F28F 1/00 <sup>(2006.01)</sup> F28D 7/16 <sup>(2006.01)</sup> F28F 13/02 <sup>(2006.01)</sup> F28F 13/12 <sup>(2006.01)</sup> F28F 13/04 <sup>(2006.01)</sup>

· Bajor, Michal

82-300 Elblag (PL)

· Fornalik-Wajs, Elzbieta

F28D 7/10 <sup>(2006.01)</sup> F28F 13/00 <sup>(2006.01)</sup> F28F 13/06 <sup>(2006.01)</sup> F28F 1/12 <sup>(2006.01)</sup>

- 32-400 Myslenice (PL)
   (74) Representative: Bury, Lech Marek Patpol ul. Nowoursynowska 162 J
  - ul. Nowoursynowska 162 J 02-776 Warszawa (PL)
- (56) References cited:
  WO-A1-2011/034249 DE-A1-102006 054 821
  GB-A- 311 092 GB-A- 2 164 438
  US-A- 3 963 071 US-A- 4 798 058
  US-A- 5 069 169 US-A- 5 902 543
  US-A1- 2010 122 797 US-A1- 2010 205 946

EP 3 067 652 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

10

#### Description

#### **Technical field**

**[0001]** The subject of the invention is a shell-and-tube heat exchanger designed to perform a heat exchange, both in single-phase and bi-phase convection mechanisms, in general applications in the area of a broadly defined thermal technology, and in particular power industry, in industrial processes, as well as in the systems for the recovery of waste heat from technological and energetic processes.

### Prior art

[0002] In the prior art, mechanisms for the hydrodynamic intensification of heat exchange are known. They include for example the use of jet inflow onto the surface of heat exchange. This mechanism allows reducing or eliminating one of the factors limiting the speed of heat exchange, which is the occurrence of a boundary layer of fluid at the surface of heat exchange. As a result of the occurrence of the boundary layer of fluid, an undesirable share of thermal conductivity in the mechanism for transferring heat through the partition increases. Thermal conductivity is less efficient than convection. By reducing or eliminating the boundary layer, the temperature gradient between the fluid and the heat exchange surface, i.e. the partition surface, is reduced. The use of fluid jet of sufficiently high speed, perfusing the heat exchange surface makes the boundary layer punctured and locally disappear. Therefore, by using jets perfusing uniformly the entire surface of heat exchange, the boundary layer can be almost completely eliminated.

**[0003]** In international application published under the number WO 2009/095896A1, entitled "Fluid microjet system", a device for generating microjets with which solids are cooled is disclosed. This device consists of a set of plates with a common channel, and microchannels reaching it. In US Patent no 5 329 994, entitled "Jet impingement exchange", an exchanger consisting of two plates separated by an additional sieve plate which, at a fluid flow, generates jets perfusing the heat exchange surfaces is disclosed.

**[0004]** It is difficult to use the jet inflow in shell-andtube heat exchangers due to the fact that in such heat exchangers a uniform coverage, with jets, of the entire surface of heat exchange is very troublesome, and not using the entire surface of heat exchange has a negative effect on the heat exchange efficiency and nullifies the benefits arising from the use of jet inflow.

**[0005]** In US Patent no US 8051900 B2, a shell-andtube heat exchanger, wherein inside the shell there is a bundle of tubes, is disclosed. In this bundle of tubes, there are tubes with a solid wall and tubes with a perforated wall. In openings of the tubes with a perforated wall, jets of a first fluid are formed and perfuse the tubes with a solid wall in which a second fluid flows. **[0006]** Although the solution disclosed in document US 8051900 was designed to increase the use of heat exchange surface perfused with jets of the first fluid, it is, however, not perfect due to the fact that by increasing the number of tubes with a perforated wall, with the same cross section of the exchanger, the number of tubes with a solid wall has to be reduced. Actually, the heat ex-

change surface is the wall surface of the solid tubes. Therefore, by increasing the use of the heat exchange surface, its size is reduced, and consequently intensifi-

cation of heat exchange is limited. [0007] Furthermore, GB 2 164 438 A discloses a shelland-tube heat exchanger for cooling exhaust gas passing in the tubes by water flowing in the shell, whereby the

<sup>15</sup> tubes are concentric double tubes with the inner tubes being perforated inducing a jet stream of gas from the inner to the outer tube. No dimensions or ratios are given in this document.

[0008] The aim of the invention is to solve the abovedescribed problems occurring in the solutions known in the prior art, in particular by providing an exchanger structure allowing the use of the heat exchange intensification by perfusion with jets, while ensuring a large heat exchange surface in relation to dimensions of the heat exchanger and making full use of the surface.

#### Essence of the invention

[0009] A heat exchanger comprising a shell and at 30 least one channel in the form of concentric tube and located inside the shell, with at least one perforated wall adapted to carry a first fluid, wherein the perforation of the wall is provided on at least a part of the surface of this perforated wall so that, as a result of the flow of the 35 first fluid, microjets are formed in perforation openings, the shell being adapted to carry a second fluid, and at least one channel having an additional solid wall surrounding the perforated wall, characterised in that the shell contains a bundle comprising at least 3 pairs of con-40 centric tubes with perforated walls and solid walls, said perforation openings in the perforated wall have dimensions smaller than 500 micrometres and a ratio of the

distance between the solid wall and the perforated wall to the average diameter of the perforation openings is in the range of 0,5 to 25.

**[0010]** The perforation openings in the perforated wall have dimensions smaller than 500 micrometres, which ensures the formation of microjets in case of most of the fluids used in a large range of pressures and flow rates used. In particular, these dimensions may be diameters.

[0011] The perforation openings in the perforated wall are constituted by circular openings made in a staggered configuration, which ensures a more uniform perfusion.
[0012] Alternatively, the perforation openings in the perforated wall are made in a checkerboard configuration.

**[0013]** The shell has preferably a cylindrical shape, and the perforated wall and the solid wall are concentric

45

50

55

10

30

35

tubes. The use of such shapes allows obtaining advantageous mechanical properties - in particular resistance to high pressures of fluids, with a relatively small wall thickness. Due to this feature the exchanger may be lighter.

[0014] Preferably, the shell is provided with auxiliary partitions positioned so as to force cross and parallelcurrent flow, i.e. so-called mixed flow of the second fluid. Such flow also promotes acceleration of heat exchange. [0015] Preferably, at least one solid wall of at least one channel is externally ribbed on at least a part of its surface. Such solution also accelerates heat exchange. Ribbing on individual channels, in particular on individual tubes, can be used, and common ribbing for all or a part of the solid walls of the channels can be also used.

**[0016]** The method for transferring heat between a first fluid and a second fluid according to the invention consists in that these fluids are introduced into the heat exchanger in which they are separated from each other by a partition. A characteristic feature of this method is that as an exchanger, the exchanger according to the invention is used. The partition is then constituted by solid walls.

**[0017]** As a first fluid and a second fluid, virtually any fluid used for transferring heat, heating and cooling can be used, including in particular water, alcohol, flue gas, air, oil, low-boiling agents, nanoliquids or nanofluids.

**[0018]** The first fluid is preferably a gas, and the second fluid is a liquid. The heat exchange between the gas and the partition is usually slower, and the use of perfusion of the partition with gas microjets accelerates the process.

**[0019]** Also preferably, the first fluid is a condensing vapour, and the second fluid is a liquid. This is also the situation in which the use of the exchanger according to the invention allows compensation of differences in heat exchange rate between the partition and the first fluid, and between the partition and the second fluid.

**[0020]** Also preferably, the first fluid is a gas, and the second fluid is a vapourising liquid. This is also the situation in which the use of the exchanger according to the invention allows compensation of differences in heat exchange rate between the partition and the first fluid, and between the partition and the second fluid.

**[0021]** Preferably, the first fluid and the second fluid are introduced into the exchanger countercurrently.

**[0022]** Preferably, the first fluid and the second fluid are introduced into the exchanger cocurrently when one of the fluids is a vapourising liquid, or when one of the fluids is a condensing vapour.

**[0023]** The advantage of the heat exchanger with a heat exchange intensification by microjets according to the invention is that its construction allows for obtaining a high efficiency of energy transport while maintaining external dimensions and mass of the exchanger thanks to the good use of the heat exchange surface while intensifying the heat exchange by perfusion of this surface with jets. With fixed thermal parameters, this solution re-

sults in a significant reduction in external dimensions and mass of the exchanger, as well as in material consumption and costs of its production. Heat exchangers made according to the invention may be combined into larger networks of exchangers. Additionally, an advantage of the method according to the invention is that it allows compensation of differences in heat exchange rate between the partition and the first fluid, and between the partition and the second fluid.

#### **Description of Figures**

[0024] The object of the invention is shown in embodiments in the drawing in which Fig. 1 shows a general 15 view of an embodiment of the shell-and-tube exchanger according to the invention, Fig. 2 shows a sectional view of this embodiment of the shell-and-tube heat exchanger according to the invention, Fig. 3 shows a schematic diagram of flow organisation of a heating agent in a bundle 20 and of a heated agent perfusing the bundle, Fig. 4a shows a perforated wall with a perforation in a staggered distribution, Fig. 4b shows a perforated wall with a perforation in a checkerboard distribution, Fig. 5 shows a distribution of tubes in a bundle inside the shell in an embodiment of 25 the exchanger according to the invention.

#### **Description of Embodiments**

**[0025]** In Fig. 1, a general view of the shell-and-tube heat exchanger with a microjet intensification of heat exchange in the bundle tubes is shown. Fig. 2 shows this exchanger in cross-section.

**[0026]** The channels carrying the first fluid are tubes 50a, 50b, 50c, with double walls. Walls of these tubes are concentric. A perforated wall 5 forms an inner tube, and a solid wall 6 forms an outer tube.

**[0027]** A port 1 for the inlet of the heating agent, i.e. the first fluid, is used to supply the fluid to the bundle of tubes 50a, 50b, 50c, more specifically to the interior of

40 the tubes with perforated walls 5. The tubes with perforated walls 5 are enclosed in the tubes with solid walls 6 covering them. The cooled first fluid is discharged through a port 2 for the outlet of the heating agent. A heated agent, i.e. the second fluid, is introduced through

<sup>45</sup> a port 3 for the inlet of the heated agent, and, after heating, is discharged through a port 4 for the outlet of the heated agent.

[0028] The first fluid from the port 1 for the heating agent inlet is distributed to three tubes with perforated walls 5. The perforation openings in these walls have a diameter of 500 micrometres or smaller. As a result of the first fluid flowing through the tube with a perforated wall 5, jets perfusing the inner surface of the tube with a solid wall 6 are generated. Thanks to this, the whole inner surface of the solid wall 6 is used as a heat exchange surface, subject to intensification due to the jet perfusion. The solid walls 6 constitute a partition between the first fluid and the second fluid. Their total surface constitutes

a heat exchange surface. The heat exchange surface is the accumulated surface of the walls 6.

**[0029]** The second fluid is carried inside the shell 7 and isolated from the first fluid by solid walls 6 of the bundle tubes 50a, 50b, 50c.

[0030] In the cross-section shown in Fig. 2, flow direction "a" of the first fluid and flow direction "b" of the second fluid are indicated. They are opposite directions. The tube bundle covered with the shell is constituted by three pairs/sets of concentric tubes 50a, 50b, 50c carrying the first fluid. The space between the inner perforated wall 5 and the outer solid wall 6 of each of the tubes 50a, 50b, 50c is not filled with the first fluid. This fluid spouts from the perforation openings 5 with jets onto the wall 6. Therefore, the space between the walls 5 and 6 is partially occupied by the first fluid jets. The staggered distribution of the perforation openings ensures that the wall 6 is perfused with jets in a very similar manner to the completely uniform one. A tube with the staggered distribution of the perforation openings is shown in Fig. 4a. Alternatively, any other distribution of openings, e.g. checkerboard configuration illustrated in Fig. 4b, can be used, although it provides a somewhat slower heat exchange than the staggered distribution.

[0031] The heat exchanger according to the invention can be used with virtually any fluids used for transferring heat, heating and cooling, including in particular water, alcohols, flue gases, air, oil, low-boiling agents, nanoliquids or nanofluids. Terms nanoliquids and nanofluids are used interchangeably to describe a fluid being a suspension of solid particles, in particular metals e.g. aluminium. [0032] The exchanger according to the invention is par-

ticularly useful in heat transfer between the gas and the liquid. Generally, gases are worse at transferring heat, and also the influence of the boundary layer on the heat exchange with a gas is more significant than in the case of a liquid. Therefore, in most known heat exchangers between the gas and the liquid separated from each other by a metal partition, a major limitation to the heat exchange rate is the intensity of the heat exchange between the partition and the gas.

**[0033]** The use of the exchanger according to the invention for the heat exchange between a gas as the first fluid and a liquid as the second fluid allows a very effective intensification of the exchange due to the elimination of "bottleneck" i.e. intensification of the heat exchange between the partition, constituted by the solid walls 6, and the gas, by eliminating the boundary layer being smashed with jets.

**[0034]** For example, with a single microjet, heat transfer coefficient for the air is approx.  $1000 \text{ W/(m^2K)}$  with an inflow of air under the pressure of 300 kPa and for the temperature difference between the partition and the fluid of 150 K.

**[0035]** For water, the coefficient is  $25\,000$  W/(m<sup>2</sup>K) with the temperature difference of 60 K and other conditions unchanged.

**[0036]** The diameter of the perforation opening which

is used in the heat exchanger according to the invention is associated with the pressure of the first fluid. This problem is complex because the choice of this diameter is also dependent on the mass flow of the first fluid. These parameters should be chosen so that as a result of fluid

flow under a predetermined pressure through a tube having a wall perforated with openings with a predetermined diameter, microjets are formed over its entire length. The diameter of the openings of up to 500 micrometres en-

<sup>10</sup> sures the formation of microjets in a wide range of pressures. The pressure drop generated during the formation of a first fluid jet in an opening of the perforated wall 5 is dependent on the opening diameter and the wall thickness. A small thickness of the wall and a parallel flow

<sup>15</sup> distribution through the perforation openings in an embodiment of the exchanger according to the invention are very advantageous because they minimise the total hydraulic resistance associated with the flow of the first fluid through the heat exchanger.

20 [0037] The distance between the perforated wall (5) and the solid wall (6) is usually determined after determining the diameter of the perforation openings. This value affects the heat exchange rate under conditions in which the formation of microjets is ensured. It can be

<sup>25</sup> chosen experimentally or by numerical analysis. The best results were obtained under conditions in which the ratio of the distance between the solid wall and the perforated wall to the diameter of the perforation opening is in the range of 0.5 to 25.

30 [0038] Generally, the aim is to maximise the number of tube pairs 50a, 50b, 50c forming a tube bundle in the shell because, along with an increase in this number, also the maximum possible heat exchange surface for predetermined dimensions of the shell 7 increases. Good
 35 packing of tubes within the shell improves compactness of the heat exchanger. Compactness is determined by a parameter defined as the ratio of heat exchange surface

of the exchanger to volume occupied by the fluid having worse properties for heat exchange. An example of tube
distribution in the cylindrical shell is shown in Fig. 5. A tube bundle arranged on a geometric grid is shown there-in, with the omission of inner perforated tubes. Together with the diameter of the outer tube and the diameter of the shell D, distance k between the outer tubes and the

<sup>45</sup> walls of the shell and the distance between the centres of the tubes, i.e. so-called scale S, are provided. Distance S is determined from the formula S = A \* dz, where A is within the range of 1.2 to 5.0. Distance k is approximately equal to half the diameter of the outer tube.

50 [0039] In the embodiment illustrated in the drawing and discussed above, the exchanger according to the invention is used in a countercurrent configuration in which the first fluid flows through the heat exchanger in a direction substantially opposite to the flow direction of the second
 55 fluid. This configuration is preferable in most cases. Sometimes, however, it is advisable to direct the flow of the two fluids in the same direction, for example, in cases where phase transformations, i.e. boiling or condensa-

15

20

25

30

35

40

45

50

55

tion, take place in the exchanger. Naturally, in this situation, the intensification of heat exchange will also occur, as a result of the perfusion of the heat exchange partition with jets of the first fluid.

**[0040]** Alternatively, in the shell of the exchanger, auxiliary partitions which will locally change, and even reverse the flow direction of the second fluid can be used. They will lead to turbulisation in the flow of the second fluid, thereby forcing a cross and parallel-current flow, i.e. so-called mixed flow of the second fluid. This modification further accelerates the heat exchange between the second fluid and the partition. This solution is appropriate if as a result of the heat exchange intensification between the first fluid and the partition, the rate of this exchange exceeds the rate of the exchange between the second fluid and the partition. The use of partitions will accelerate the resultant heat exchange.

**[0041]** In addition, the solid tubes 6 can be externally ribbed. Selected ones or all of the tubes can have individual ribbing on part or on the whole surface, or they can have a common ribbing resembling a lamella.

**[0042]** It is clear that the above embodiments and drawings illustrating them were provided only for ease of explanation of the essence of the invention, the proper scope of which is defined by the patent claims. This scope includes methods and heat exchangers in which various shapes of openings and their sizes in the perforated wall, and various densities and distributions, as well as various distributions and number of tubes in a bundle, or different geometrical dimensions of the exchanger can be used. There is not any reason to interpret these given examples as limiting in any way.

## Claims

 A heat exchanger comprising a shell (7) and at least one channel located inside the shell and in the form of concentric tubes, with at least one perforated wall (5) adapted to carry a first fluid, wherein the perforation of the wall is provided on at least a part of the surface of this perforated wall (5) so that, as a result of the flow of the first fluid, microjets are formed in perforation openings, the shell (7) being adapted to carry a second fluid, and at least one channel having an additional solid wall (6) surrounding the perforated wall (5),

## characterised in that

the shell (7) contains a bundle comprising at least 3 pairs of concentric tubes (50a, 50b, 50c) with perforated walls (5) and solid walls (6), said perforation openings in the perforated wall (5) have dimensions smaller than 500 micrometres and a ratio of the distance between the solid wall (6) and the perforated wall (5) to the average diameter of the perforation openings is in the range of 0,5 to 25.

2. The heat exchanger according to claim 1 , charac-

**terised in that** the perforation openings in the perforated wall are constituted by circular openings made in a staggered configuration.

- 3. The heat exchanger according to claim 1, characterised in that the perforation openings in the perforated wall are constituted by circular openings made in a checkerboard configuration.
- 10 4. The heat exchanger according to any one of claims 1 to 3, characterised in that the shell has a cylindrical shape, and the perforated wall (5) and the solid wall (6) form a pair of concentric tubes (50a, 50b, 50c).
  - 5. The heat exchanger according to any of claims 1-4, characterised in that the shell (7) is provided with auxiliary partitions positioned so as to force cross and parallel-current flow of the second fluid in the shell (7).
  - 6. The heat exchanger according to claim 5, characterised in that the solid wall (6) of at least one channel is externally ribbed on at least a part of its surface.
  - 7. A method for transferring heat between the first fluid and the second fluid, wherein these fluids are introduced into a heat exchanger in which they are separated from each other by a partition, characterised in that as an exchanger, the exchanger as defined in any one of claims 1 to 6 is used.
  - **8.** The method according to claim 7, wherein the first fluid is a gas, and the second fluid is a liquid.
  - **9.** The method according to claim 7, wherein the first fluid is a condensing vapour, and the second fluid is a liquid.
  - **10.** The method according to claim 7, wherein the first fluid is a gas, and the second fluid is a vapourising liquid.
  - **11.** The method according to any one of claims 7 to 10, **characterised in that** the first fluid and the second fluid are introduced into the exchanger countercurrently.
  - **12.** The method according to claim 9 or 10, **characterised in that** the first fluid and the second fluid are introduced into the exchanger cocurrently.

### Patentansprüche

 Ein Wärmetauscher, umfassend ein Gehäuse (7) und mindestens einen Kanal, der innerhalb des Gehäuses und in Form von konzentrischen Rohren an-

10

15

20

30

40

45

50

55

geordnet ist,

mit mindestens einer perforierten Wand (5), die zum Führen eines ersten Fluides geeignet ist, wobei die Perforation der Wand auf mindestens einem Teil der Oberfläche dieser perforierten Wand (5) vorgesehen ist, so dass infolge der Strömung des ersten Fluides Mikrostrahlen in Perforationsöffnungen gebildet werden, wobei das Gehäuse (7) zum Führen eines zweiten Fluides geeignet ist, und mindestens ein Kanal über eine zusätzliche feste Wand (6), die die perforierte Wand (5) umgibt, verfügt, **dadurch gekennzeichnet, dass** 

das Gehäuse (7) ein Bündel enthält, das mindestens 3 Paar konzentrische Rohre (50a, 50b, 50c) mit perforierten Wänden (5) und festen Wänden (6) umfasst, wobei die Perforationsöffnungen in der perforierten Wand (5) Abmessungen kleiner als 500 Mikrometer aufweisen und ein Verhältnis des Abstands zwischen der festen Wand (6) und der perforierten Wand (5) zum durchschnittlichen Durchmesser der Perforationsöffnungen im Bereich von 0,5 bis 25 liegt.

- Der Wärmetauscher nach Anspruch 1, dadurch gekennzeichnet, dass die Perforationsöffnungen in <sup>25</sup> der perforierten Wand aus kreisförmigen Öffnungen bestehen, die versetzt angeordnet sind.
- 3. Der Wärmetauscher nach Anspruch 1, dadurch gekennzeichnet, dass die Perforationsöffnungen in der perforierten Wand aus kreisförmigen Öffnungen bestehen, die in einer Schachbrettkonfiguration ausgeführt sind.
- Der Wärmetauscher nach einem der Ansprüche 1 <sup>35</sup> bis 3, dadurch gekennzeichnet, dass das Gehäuse eine zylindrische Form aufweist und die perforierte Wand (5) und die feste Wand (6) ein Paar konzentrische Rohre (50a, 50b, 50c) bilden.
- 5. Der Wärmetauscher nach einem der Ansprüche 1-4, dadurch gekennzeichnet, dass das Gehäuse (7) mit Hilfstrenwänden versehen ist, die so angeordnet sind, dass sie den Quer- und Parallelstrom des zweiten Fluides in dem Gehäuse (7) erzwingen.
- 6. Der Wärmetauscher nach Anspruch 5, dadurch gekennzeichnet, dass die feste Wand (6) mindestens eines Kanals auf mindestens einem Teil ihrer Oberfläche außen gerippt ist.
- 7. Ein Verfahren zum Übertragen von Wärme zwischen dem ersten Fluid und dem zweiten Fluid, wobei diese Fluide in einen Wärmetauscher eingeführt werden, in dem sie durch eine Trennwand voneinander getrennt sind,

dadurch gekennzeichnet, dass als Wärmetauscher der Wärmetauscher, wie in einem der Ansprüche 1 bis 6 definiert, verwendet wird.

- 8. Das Verfahren nach Anspruch 7, wobei das erste Fluid ein Gas ist und das zweite Fluid eine Flüssigkeit ist.
- **9.** Das Verfahren nach Anspruch 7, wobei das erste Fluid ein kondensierender Dampf ist und das zweite Fluid eine Flüssigkeit ist.
- - **10.** Das Verfahren nach Anspruch 7, wobei das erste Fluid ein Gas ist und das zweite Fluid eine verdampfende Flüssigkeit ist.
- 11. Das Verfahren nach einem der Ansprüche 7 bis 10, dadurch gekennzeichnet, dass das erste Fluid und das zweite Fluid im Gegenstrom in den Wärmetauscher eingebracht werden.
- 12. Das Verfahren nach Anspruch 9 oder 10, dadurch gekennzeichnet, dass das erste Fluid und das zweite Fluid gleichzeitig in den Wärmetauscher eingebracht werden.

## Revendications

- 1. Un échangeur de chaleur comprenant une coque (7) et au moins un canal situé à l'intérieur de la coque et sous la forme de tubes concentriques,
- avec au moins une paroi perforée (5) adaptée pour transporter un premier fluide, dans lequel la perforation de la paroi est prévue sur au moins une partie de la surface de cette paroi perforée (5) de sorte que, du fait de l'écoulement du premier fluide, des micro-jets soient formés dans des ouvertures de perforation, la coque (7) étant adaptée pour transporter un second fluide, et au moins un canal ayant une paroi pleine supplémentaire (6) entourant la paroi perforée (5), **caractérisé en ce que**

la coque (7) contient un faisceau comprenant au moins 3 paires de tubes concentriques (50a, 50b, 50c) à parois perforées (5) et parois pleines (6), lesdites ouvertures de perforation dans la paroi perforée (5) ont des dimensions inférieures à 500 micromètres et le rapport entre la distance entre la paroi pleine (6) et la paroi perforée (5) et le diamètre moyen des ouvertures de perforation est compris entre 0,5 et 25.

- - L'échangeur de chaleur selon la revendication 1, caractérisé en ce que les ouvertures de perforation dans la paroi perforée sont constituées par des ouvertures circulaires réalisées dans une configuration en quinconce.
- 3. L'échangeur de chaleur selon la revendication 1, caractérisé en ce que les ouvertures de perforation

10

15

20

30

dans la paroi perforée sont constituées par des ouvertures circulaires réalisées dans une configuration en damier.

- 4. L'échangeur de chaleur selon l'une quelconque des revendications 1 à 3, **caractérisé en ce que** la coque a une forme cylindrique, et la paroi perforée (5) et la paroi pleine (6) forment une paire de tubes concentriques (50a, 50b, 50c).
- L'échangeur de chaleur selon l'une quelconque des revendications 1 à 4, caractérisé en ce que la coque (7) est munie de cloisons auxiliaires positionnées de manière à forcer la circulation d'un courant transversal et parallèle du second fluide dans la coque (7).
- L'échangeur de chaleur selon la revendication 5, caractérisé en ce que la paroi pleine (6) d'au moins un canal est nervuré extérieurement sur au moins une partie de sa surface.
- 7. Une méthode pour transférer de la chaleur entre le premier fluide et le deuxième fluide, dans laquelle ces fluides sont introduits dans l'échangeur de chaleur dans lequel ils sont séparés l'un de l'autre par une cloison,
   caractérisé en ce que l'échangeur tel que défini dans l'une quelconque des revendications 1 à 6 est
- La méthode selon la revendication 7, dans laquelle le premier fluide est un gaz et le second fluide est un liquide.

utilisé comme échangeur.

- La méthode selon la revendication 7, dans laquelle <sup>35</sup> le premier fluide est une vapeur de condensation et le second fluide est un liquide.
- La méthode selon la revendication 7, dans laquelle le premier fluide est un gaz et le second fluide est 40 un liquide de vaporisation.
- 11. La méthode selon l'une quelconque des revendications 7 à 10, caractérisée en ce que le premier fluide et le second fluide sont introduits dans l'échangeur
   45 à contre-courant.
- La méthode selon la revendication 9 ou 10, caractérisée en ce que le premier fluide et le second fluide sont introduits dans l'échangeur en même temps.

12



Fig. 1



Fig. 2







Fig. 4b



Fig. 5

## **REFERENCES CITED IN THE DESCRIPTION**

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

## Patent documents cited in the description

- WO 2009095896 A1 [0003]
- US 5329994 A [0003]
- US 8051900 B2 [0005]

- US 8051900 B [0006]
- GB 2164438 A [0007]

10