



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
30.11.2022 Bulletin 2022/48

(51) International Patent Classification (IPC):
G01S 13/931 (2020.01) G01S 17/931 (2020.01)
G06K 9/00 (2022.01)

(21) Application number: **21176539.1**

(52) Cooperative Patent Classification (CPC):
G01S 13/726; G01S 7/4808; G01S 13/931;
G01S 17/931; G06V 20/56; G01S 13/44;
G01S 13/58

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
 Designated Extension States:
BA ME
 Designated Validation States:
KH MA MD TN

(72) Inventors:
 • **RÓZEWICZ, Maciej**
30-702 Kraków (PL)
 • **POREBSKI, Jakub**
30-669 Kraków (PL)
 • **KOGUT, Krzysztof**
30-612 Kraków (PL)

 (74) Representative: **Manitz Finsterwald**
Patent- und Rechtsanwaltspartnerschaft mbB
Martin-Greif-Strasse 1
80336 München (DE)

(71) Applicant: **Aptiv Technologies Limited**
St. Michael (BB)

(54) **METHODS AND SYSTEMS FOR OCCUPANCY STATE DETECTION**

(57) A computer implemented method for occupancy state detection in an area for a pre-determined point in time, the following steps carried out by computer hardware components: determining a probability distribution over a list of possible occupancy states of the area at a previous point in time; determining measurement data

related to the area at the pre-determined point in time; and determining a probability distribution over the list of possible occupancy states of the area at the pre-determined point in time based on the measurement data and the probability distribution over the list of possible occupancy states of the area at the previous point in time.




Fig. 3

Description

FIELD

5 **[0001]** The present disclosure relates to methods and systems for occupancy state detection.

BACKGROUND

10 **[0002]** Various sensors such as radar sensors or LIDAR sensors may be used in automotive applications to monitor the environment of a vehicle. In the environment of the vehicle an area may be occupied by different objects, for example other vehicles, pedestrians, barriers or the like, that may influence safety and reliability of driver assistant systems. Thus, it may be desired to know whether the area is occupied and if so, which occupancy state is valid for that area. However, reliable occupancy state detection suffers from complexity and high computational effort.

15 **[0003]** Accordingly, there is a need to provide efficient methods and systems for occupancy state detection.

SUMMARY

20 **[0004]** The present disclosure provides a computer implemented method, a computer system, a vehicle and a non-transitory computer readable medium according to the independent claims. Embodiments are given in the subclaims, the description and the drawings.

25 **[0005]** In one aspect, the present disclosure is directed at a computer implemented method for occupancy state detection in an area for a pre-determined point in time, the method comprises the following steps performed (in other words: carried out) by computer hardware components: determining a probability distribution over a list of possible occupancy states of the area at a previous point in time; determining measurement data related to the area at the pre-determined point in time; and determining a probability distribution over the list of possible occupancy states of the area at the pre-determined point in time based on the measurement data and the probability distribution over the list of possible occupancy states of the area at the previous point in time. The list of possible occupancy states comprises a static occupancy state, a dynamic occupancy state, a free-space state, a first uncertainty state between the static occupancy state and the dynamic occupancy state, a second uncertainty state between the static occupancy state and the free-space state, a third uncertainty state between the dynamic occupancy state and the free-space state, and an unknown occupancy state.

30 **[0006]** In other words, the probability distribution at the previous point in time of the area is determined over the list of defined possible occupancy states, i.e. states that for example describe whether an object is present in the area. The previous point in time may be immediately before the pre-determined time (in other words: no further point in time is between the previous point in time and the pre-determined point in time). It will be understood that a discrete sequence of points in time may be used, for example equidistant points in time, for example a point in time every pre-determined amount of seconds, for example every second, or every 1/10 of a second (i.e. 100 ms), or the like. The pre-determined point in time may be a current point in time or an arbitrary point in time. The pre-determined point in time may directly follow after the previous point in time (in other words: no further point in time is between the pre-determined point in time and the previous point in time). Additionally, measurement data at the pre-determined point in time of the area may be measured by a sensor. The sensor may be or may include a radar sensor and/or a LIDAR sensor. The probability distribution at the pre-determined point in time of the area may be determined over the list of defined possible occupancy states, wherein the probability distribution at the pre-determined point in time of the area may be dependent on the probability distribution at the previous point in time of the area and the measurement data at the pre-determined point in time of the area.

45 **[0007]** The area may be an environment of a robot or a vehicle. The area may be of variable size or the area may be a specific area (or sector) of interest, for example in front of the robot or the vehicle.

50 **[0008]** Occupancy state detection in the area may be understood as a combination of object detection and estimation of a possible state of the object. In other words, if there is an object detected in the area, then the area may be defined as occupied. Otherwise, if the area is not occupied, the area may be defined as free-space. If the area is occupied, the object in the area may have one possible state, i.e. one occupancy state. The occupancy state may be one of the defined possible occupancy states from the list of possible occupancy states as described herein. The static occupancy state may describe a state wherein the occupancy state may be in a steady state or a quasi-steady state, i.e. the occupancy state may remain constant with respect to time (in other words: objects with the static occupancy state do not move with respect to time). The dynamic occupancy state may describe a state wherein the occupancy state may have a changing behavior with respect to time (in other words: objects with the dynamic occupancy state may move with respect to time). Thus, the difference between the static occupancy state and the dynamic occupancy state may be on the behavior of the respective occupancy state with respect to time. For each of the uncertainty states described in the list of possible

occupancy states, it may not be clear which of the respective two possible occupancy states the object has. For the unknown occupancy state, it may not be known whether the area is occupied or a free-space.

[0009] The probability distribution may provide a probability for each of the states. The probabilities over all probabilities may sum up to 1 (i.e. 100%), or the probabilities may sum up to any different value, so that the respective probability does not provide a probability as such, but the relative values of the respective probabilities of the states provide information about which state is more likely than another.

[0010] According to an embodiment, the probability distribution over the list of possible occupancy states of the area at the previous point in time comprises a pre-determined initial state distribution over the list of possible occupancy states of the area.

[0011] According to an embodiment, the initial state distribution over the list of possible occupancy states of the area comprises an equal distribution over the list of possible occupancy states of the area.

[0012] The equal distribution over the list of possible occupancy states of the area means that the possibility of each of the possible states in the initial state is the same.

[0013] According to an embodiment, the probability distribution over the list of possible occupancy states of the area at the previous point in time is determined based on measurement data related to the area at the previous point in time and a probability distribution over the list of possible occupancy states of the area at a further point in time preceding the previous point in time.

[0014] In other words: the probability distribution at the previous point in time of the area is determined over the list of defined possible occupancy states, wherein the probability distribution at the previous point in time of the area is dependent on the probability distribution at the further previous point in time of the area and the measurement data at the previous point in time of the area.

[0015] The further point in time may be immediately before the previous point in time (in other words: no another further point in time is between the further point in time and the previous point in time). The previous point in time may directly follow after the further point in time (in other words: no another further point in time is between the previous point in time in time and the further point in time).

[0016] There may be a plurality of further points in time preceding the further point in time. The determination of a probability distribution at the further points in time of the area may then be carried out similar to the determination of the probability distribution at the pre-determined point in time or the determination of the probability distribution at the previous point in time.

[0017] According to an embodiment, the probability distribution over the list of possible occupancy states of the area at the pre-determined point in time is determined further based on a transition matrix comprising a plurality of state transition probabilities between possibly occupancy states.

[0018] The transition matrix may be a transition matrix of a Markov model, and the method according to various embodiments may be carried out according to the Markov model.

[0019] The transition matrix may indicate probabilities of state transitions under the assumption that no sensor data is available.

[0020] The plurality of state transition probabilities may be a respective state transition probability from each of a first occupancy state of the possible occupancy states to a second occupancy state of the possible occupancy states. The first occupancy state may be identical to second occupancy state or the first occupancy state may be different from second occupancy state.

[0021] According to an embodiment, the following state transition probabilities are different from zero: a state transition probability from the static occupancy state into the static occupancy state; a state transition probability from the static occupancy state into the first uncertainty state between the static occupancy state and the dynamic occupancy state; a state transition probability from the static occupancy state into the second uncertainty state between the static occupancy state and the free-space state; a state transition probability from the dynamic occupancy state into the dynamic occupancy state; a state transition probability from the dynamic occupancy state into the first uncertainty state between the static occupancy state and the dynamic occupancy state; a state transition probability from the dynamic occupancy state into the third uncertainty state between the dynamic occupancy state and the free-space state; a state transition probability from the free-space state into the free-space state; a state transition probability from the free-space state into the second uncertainty state between the static occupancy state and the free-space state; a state transition probability from the free-space state into the third uncertainty state between the dynamic occupancy state and the free-space state; a state transition probability from the first uncertainty state between the static occupancy state and the dynamic occupancy state into the first uncertainty state between the static occupancy state and the dynamic occupancy state; a state transition probability from the first uncertainty state between the static occupancy state and the dynamic occupancy state into the unknown occupancy state; a state transition probability from the second uncertainty state between the static occupancy state and the free-space state into the second uncertainty state between the static occupancy state and the free-space state; a state transition probability from the second uncertainty state between the static occupancy state and the free-space state into the unknown occupancy state; a state transition probability from the third uncertainty state between the

dynamic occupancy state and the free-space state into third uncertainty state between the dynamic occupancy state and the free-space state; a state transition probability from the third uncertainty state between the dynamic occupancy state and the free-space state into the unknown occupancy state; a state transition probability from the unknown occupancy state into the unknown occupancy state (which may be equal to 1).

5 **[0022]** All other possible state transition probabilities may be zero, i.e. a state transition probability from the static occupancy state into the dynamic occupancy state or into the free-space state or into the third uncertainty state between the dynamic occupancy state and the free-space state or into the unknown occupancy state; a state transition probability from the dynamic occupancy state into the static occupancy state or into the free-space state or into the second uncertainty state between the static occupancy state and the free-space state or into the unknown occupancy state; a state transition probability from the free-space state into the static occupancy state or into the dynamic occupancy state or into the first uncertainty state between the static occupancy state and the dynamic occupancy state or into the unknown occupancy state; a state transition probability from the first uncertainty state between the static occupancy state and the dynamic occupancy state into the static occupancy state or into the dynamic occupancy state or into the free-space state or into the second uncertainty state between the static occupancy state and the free-space state or the third uncertainty state between the dynamic occupancy state and the free-space state; a state transition probability from the second uncertainty state between the static occupancy state and the free-space state into the static occupancy state or into the dynamic occupancy state or into the free-space state or into the first uncertainty state between the static occupancy state and the dynamic occupancy state and the free-space state; a state transition probability from the third uncertainty state between the dynamic occupancy state and the free-space state into the static occupancy state or into the dynamic occupancy state or into the free-space state or into the first uncertainty state between the static occupancy state and the dynamic occupancy state or into the second uncertainty state between the static occupancy state and the free-space state; a transition from the unknown occupancy state into the static occupancy state or into the dynamic occupancy state or into the free-space state or into the first uncertainty state between the static occupancy state and the dynamic occupancy state or into the second uncertainty state between the static occupancy state and the free-space state or into the third uncertainty state between the dynamic occupancy state and the free-space state.

[0023] In other words: there may be no state transition probability between the static occupancy state and the dynamic occupancy state and the free-space state and the unknown occupancy state directly. There may be no state transition probability between the static occupancy state or the dynamic occupancy state or the free-space state into an uncertainty state, wherein the uncertainty state is not between the respective static occupancy state or not between the respective dynamic occupancy state or not between the respective free-space state and the static occupancy state or the dynamic occupancy state or the free-space state. There may be no state transition probability from an uncertainty state back to the static occupancy state or the dynamic occupancy state or the free-space state. There may be no state transition probability from the unknown occupancy state into any other possible state, except the unknown occupancy state itself.

35 **[0024]** According to an embodiment, the transition matrix is dependent of an estimated velocity of an object in the area.

[0025] The estimated velocity of an object in the area may also be referred to as estimated cell velocity.

[0026] According to an embodiment, the probability distribution over the list of possible occupancy states of the area at the pre-determined point in time is determined further based on an observation matrix comprising observation emission probabilities.

40 **[0027]** The observation matrix may be an observation matrix of a Markov model, and the method according to various embodiments may be carried out according to the Markov model.

[0028] The observation matrix may introduce sensor data to the method.

[0029] The observation emission probabilities may be a respective observation emission probability from each of a probability distribution over the list of possible occupancy states of the area at the pre-determined point in time to an observation state over a list of possible observation states. The list of possible observation states may be dependent of the sensor, used for the observation.

[0030] According to an embodiment, the area comprises a cell of an occupancy grid, the occupancy grid comprising a plurality of further cells.

50 **[0031]** In other words, the area may be represented by a cell, wherein the plurality of cells may represent the occupancy grid. Each of the further cells represents a respective further area. The method described herein may (also) be carried out for each of the further cells (in other words: for the further areas). The cell and each of the further cells may be in one of the possible states, and the states may be different for different cells.

[0032] According to an embodiment, the measurement data is determined based on a LIDAR sensor and the measurement data comprises an uncertainty information between a static occupancy and a dynamic occupancy or a free-space information.

55 **[0033]** The LIDAR sensor may measure a range or a distance between the sensor and a vehicle or an object. Measurement data from a LIDAR sensor may also comprise an azimuth and an elevation angle of a vehicle or an object relatively to the sensor. The measurement data recorded from the LIDAR sensor may be very detailed and may include

fine and accurate information about objects at a great distance. Ambient lighting may not influence the quality of the captured information by LIDAR, thus the results at day and night may be without any loss of performance due to disturbances such as shadows, sunlight or headlight glare.

[0034] According to an embodiment, the measurement data is determined based on a radar sensor and the measurement data comprises a static occupancy information, a dynamic occupancy information, an uncertainty information between a static occupancy and a dynamic occupancy, or a free-space information.

[0035] Radar sensors may be impervious to adverse or bad weather conditions, working reliably in dark, wet or even foggy weather. Radar sensors may be able to identify a distance, a direction and a relative speed of vehicles or objects. The direction may be determined by the azimuth and elevation, wherein the azimuth and elevation may be measured by radar sensors.

[0036] According to an embodiment, the observation matrix is dependent on at least one of a detection range rate from the radar sensor and a distance from the radar sensor.

[0037] The range rate may be the velocity, i.e. the relative speed. The range rate may describe the rate that a vehicle or object moves toward or away from the radar sensor.

[0038] In another aspect, the present disclosure may be directed at a computer system, said computer system comprising a plurality of computer hardware components configured to carry out several or all steps of the computer implemented method described herein.

[0039] The computer system may comprise a plurality of computer hardware components (for example a processor, for example processing unit or processing network, at least one memory, for example memory unit or memory network, and at least one non-transitory data storage). It will be understood that further computer hardware components may be provided and used for carrying out steps of the computer implemented method in the computer system. The non-transitory data storage and/or the memory unit may comprise a computer program for instructing the computer to perform several or all steps or aspects of the computer implemented method described herein, for example using the processing unit and the at least one memory unit.

[0040] In another aspect, the present disclosure is directed to a vehicle, comprising the computer system described herein and a sensor, wherein the measurement data is determined based on an output of the sensor. The sensor may be a radar system and/or a LIDAR system.

[0041] The vehicle can be a car, a truck or a motorcycle and the sensor may be mounted on the vehicle. The sensor may be directed to an area in front or in the rear or at a side of the vehicle. Measurement data may be captured by the sensor when the vehicle is moving.

[0042] In another aspect, the present disclosure is directed at a non-transitory computer readable medium comprising instructions for carrying out several or all steps or aspects of the computer implemented method described herein. The computer readable medium may be configured as: an optical medium, such as a compact disc (CD) or a digital versatile disk (DVD); a magnetic medium, such as a hard disk drive (HDD); a solid state drive (SSD); a read only memory (ROM), such as a flash memory; or the like. Furthermore, the computer readable medium may be configured as a data storage that is accessible via a data connection, such as an internet connection. The computer readable medium may, for example, be an online data repository or a cloud storage.

[0043] The present disclosure is also directed at a computer program for instructing a computer to perform several or all steps or aspects of the computer implemented method described herein.

[0044] With the methods and system described herein, hidden Markov models may be used as a method for dynamic and static occupancy discrimination in an occupancy grid method framework. For example, each cell of the occupancy grid may be treated separately by defining the possible states and transitions of each cell and modelling the sensor data observation matrix.

DRAWINGS

[0045] Exemplary embodiments and functions of the present disclosure are described herein in conjunction with the following drawings, showing schematically:

Fig. 1 a graphical representation of a Markov Chain;

Fig. 2 a visualization of the computation of a single probability distribution;

Fig. 3 an illustration of a state transition graph;

Fig. 4 a flow diagram illustrating a method for occupancy state detection according to various embodiments; and

Fig. 5 a computer system with a plurality of computer hardware components configured to carry out steps of a computer

implemented method for object detection according to various embodiments.

DETAILED DESCRIPTION

5 **[0046]** Occupancy state detection of objects or the like may be used in different technical fields. For instance, path planning and collision avoidance in robotic applications or object detection for driving assistance systems in the automotive industry may use methods and systems based on occupancy state detection.

10 **[0047]** The environment of a robot or a vehicle for example may comprehend a plurality of different objects or the like with different states, for example a static state for buildings, trees or the like, a dynamic state for driving vehicles and moving pedestrians or the like or even an unknown state if it is not recognizable or measurable what the object or the like behavior is. To detect the different states of the objects, the environment of the robot, the vehicle or the like may be divided by means of a grid into an evenly spaced field of a plurality of cells. Each cell of the grid may represent the presence of an obstacle, an object, a part of an obstacle or a part of an object at that location in the environment by a binary random variable. For each of these cells or sections, an occupancy state may be estimated that may specify whether
15 the cell is occupied. This method may be referred to as an occupancy grid mapping. Occupancy grid methods may compute approximate posterior estimates for these random variables.

[0048] In other words, an occupancy grid mapping refers to a family of methods in probabilistic robotics for mobile robots or vehicles for example which address the problem of generating maps from noisy and uncertain sensor measurement data, with the assumption that the robot pose or vehicle position is known.

20 **[0049]** For a reliable detection of occupancy states in dynamic environments, a robust model may be useful to obtain an accurate occupancy state estimation. For example, Markov chain model-based approaches may be used. A Markov chain model may predict that the probability of switching from a current state will not vary as a function of previous states. In probability theory, a Markov model may be a stochastic model used to model pseudo-randomly changing systems. It may be assumed that future states depend only on the current state, not on the events that occurred before it (i.e. it
25 assumes the Markov property). This assumption may enable reasoning and computation with the model that would otherwise be intractable. For this reason, in the fields of predictive modelling and probabilistic forecasting, it may be desirable for a given model to exhibit the Markov property.

[0050] An enhancement of the Markov chain method may be a Hidden Markov Model (HMM). HMM may be a statistical Markov Model in which a modeled system may be assumed to be a Markov process X with unobservable ("hidden")
30 occupancy states. HMM may assume that there may be another process, an observation, Y whose behavior depends (probabilistically) on the process X . The main idea of HMM method may be to extract information about the process X by observing the process Y .

[0051] The Hidden Markov Model (HMM) may use occupancy grid maps created at different discrete time steps ($t = 0, 1, 2, \dots$) as observations. At each discrete time step t , the system may be in some internal ("hidden") occupancy state
35 h_t and a measurement (which may also be referred to as an observation) m_t may be emitted based only on h_t . The system may transit to a new occupancy state h_{t+1} from time step t to time step $t+1$, and the process may repeat. This may be called Markov Chain and is presented graphically in Fig. 1.

[0052] Fig. 1 shows a graphical representation of a Markov Chain 100. Fig. 1 is divided into two sections by a bold line, wherein the area above the bold line shows an actual state (which may also be referred to as a hidden layer) and
40 the area below the bold line shows a measurement (which may also be referred to as an observation). The actual state comprises a plurality of occupancy states h_1 102, h_2 104, h_3 106, h_4 108 at discrete time steps t that are connected in a way that the occupancy state of a point in time depends on the occupancy state of a previous point in time, i.e. the point in time of the previous point in time is directly before the point in time. The connections between the occupancy states are represented by arrows q_{12} 126, q_{23} 128, q_{34} 130 and q_{45} 132 that indicate the transition from the occupancy state h_{t-1} at the previous point in time $t-1$ to the occupancy state h_t at the present point in time. For example, the arrow
45 q_{34} 130 connects the occupancy state h_3 106 with the occupancy state h_4 108. Furthermore, each of the occupancy states h_1 102, h_2 104, h_3 106, h_4 108 in the upper part of Fig. 1 is connected to a corresponding measurement m_1 110, m_2 112, m_3 114, m_4 116 in the lower part of Fig. 1 by an arrow. The arrows b_1 118, b_2 120, b_3 122 and b_4 124 indicate that the measurement m_t occurs if the occupancy state h_t is present.

[0053] To apply the Hidden Markov Model (HMM) framework, some variables and operators may be defined beforehand. A list of possible occupancy states Ω may be assumed to be finite. The list of occupancy states Ω may consist of
50 $\{S, D, F, SD, SF, DF, SDF\}$, wherein the occupancy states may be defined as a static occupancy state S , a dynamic occupancy state D , a free-space state F , a first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D , a second uncertainty state SF between the static occupancy state S and the free-space state F , a third uncertainty state DF between the dynamic occupancy state D and the free-space state F , and an unknown occupancy state SDF .

[0054] An initial state distribution $p(\Omega_1 = \omega), \forall \omega \in \Omega$ over the list of possible occupancy states of the area may be pre-determined.

[0055] State transition probabilities $p_{ij}(\Omega_{t+1} = \omega' | \Omega_t = \omega), \forall \omega, \omega' \in \Omega$ may be defined that indicate how likely it is that the occupancy state ω' occurs if the previous occupancy state ω was present. These annotate the right-going arcs in Fig. 2.

[0056] A set of observations O may be assumed to be finite. The observation emission probabilities $b(O_t = o | \Omega_t = \omega), \forall \omega \in \Omega, o \in O$ may indicate how likely it is that the observation o occurs if the occupancy state ω is present. These annotate the down-going arcs in Fig. 2.

[0057] If Ω and O are finite, the initial state distribution p may be represented as a vector p of size $|\Omega|$.

[0058] In Fig. 2, the state transition probabilities p_{ij} may indicate how likely it is that the occupancy state ω_j at a present point in time t occurs if the occupancy state ω_i was present at a previous point in time $t-1$.

[0059] The transition probabilities form a transition matrix P of size $|\Omega| \times |\Omega|$, wherein each row i is the multinomial of the next state given that the current state is i . Similarly, the observation emission probabilities form an observation matrix Q of size $|\Omega| \times |O|$, wherein each row i is a multinomial distribution over the observations, given the occupancy state.

[0060] Together b_0, P and Q may form the model of the HMM.

[0061] Forward calculation of a j -th occupancy state probability $\alpha_t(j)$ may be done in each step by the formula:

$$\alpha_t(j) = \sum_{i=1}^{|\Omega|} \alpha_{t-1}(i) p_{i \rightarrow j} b_j(O_t)$$

[0062] Fig. 2 shows a visualization of the computation of a single probability distribution 200. The computation may be performed by a computer implemented method for occupancy state detection in an area for a pre-determined point in time t . The following steps carried out by computer hardware components: determining a probability distribution $\alpha_{t-1}(1)$ 204, $\alpha_{t-1}(2)$ 206, $\alpha_{t-1}(3)$ 208 till $\alpha_{t-1}(N)$ 210 over a list of possible occupancy states of the area at a previous point in time $t-1$; determining measurement data (in other words: observation) o_t 212 related to the area at the pre-determined point in time t ; and determining a probability distribution $\alpha_t(j)$ 202 over the list of possible occupancy states of the area at the pre-determined point in time t based on the measurement data of 212 and the probability distribution $\alpha_{t-1}(1)$ 204, $\alpha_{t-1}(2)$ 206, $\alpha_{t-1}(3)$ 208 till $\alpha_{t-1}(N)$ 210 over the list of possible occupancy states of the area at the previous point in time;

[0063] In other words: the j -th probability distribution $\alpha_t(j)$ 202 at a pre-determined point in time t may be calculated by summing up all previous probability distributions $\alpha_{t-1}(1)$ 204, $\alpha_{t-1}(2)$ 206, $\alpha_{t-1}(3)$ 208 till $\alpha_{t-1}(N)$ 210 in a previous point in time $t-1$, weighted by their state transition probabilities p_{1j} 214, p_{2j} 216, p_{3j} 218 and p_{Nj} 220 and further multiplied by the observation emission probability $b_j(o_t)$ 222, wherein o_t 212 is the observation at the pre-determined point in time t .

[0064] The area may be represented by a cell, wherein the plurality of cells may represent the occupancy grid. Each of the plurality of cells from the occupancy grid may be treated as a separate system. The steps of the method described above may be performed in each of the plurality of cells from the occupancy grid. Each of the plurality of cells from the occupancy grid may be observed by a radar sensor or a LIDAR sensor.

[0065] If the list of possible occupancy states Ω is finite and defined for example as $\Omega = \{S, D, F, SD, SF, DF, SDF\}$, then the possible transitions between occupancy states may be presented graphically in form of a graph. An illustration of a state transition graph 300 is presented in Fig. 3. The possible occupancy states Ω may be defined as described herein, i.e. a static occupancy state S , a dynamic occupancy state D , a free-space state F , a first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D , a second uncertainty state SF between the static occupancy state S and the free-space state F , a third uncertainty state DF between the dynamic occupancy state D and the free-space state F and an unknown occupancy state SDF . The possible occupancy states are connected by a plurality of arrows which represents a plurality of state transition probabilities between possibly occupancy states. Those state transition probabilities between possibly occupancy states may be defined as presented in the following transition matrix P :

$$P = \begin{bmatrix} p_{S \rightarrow S} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & p_{D \rightarrow D} & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & p_{F \rightarrow F} & 0 & 0 & 0 & 0 \\ p_{S \rightarrow SD} & p_{D \rightarrow SD} & 0 & p_{SD \rightarrow SD} & 0 & 0 & 0 \\ p_{S \rightarrow SF} & 0 & p_{F \rightarrow SF} & 0 & p_{SF \rightarrow SF} & 0 & 0 \\ 0 & p_{D \rightarrow DF} & p_{F \rightarrow DF} & 0 & 0 & p_{DF \rightarrow DF} & 0 \\ 0 & 0 & 0 & p_{SD \rightarrow SDF} & p_{SF \rightarrow SDF} & p_{DF \rightarrow SDF} & 1 \end{bmatrix}$$

[0066] The probabilities provided in the transition matrix P can be treated as equivalent of a decay or a forgetting factor (which may provide that without measurement data, the knowledge of the states would decay or would be forgotten).

[0067] As shown in the formula above, the following state transition probabilities are different from zero and defined as: a state transition probability $p_{S \rightarrow S}$ 302 from the static occupancy state S into the static occupancy state S, a state transition probability $p_{S \rightarrow SD}$ 304 from the static occupancy state S into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D, a state transition probability $p_{S \rightarrow SF}$ 306 from the static occupancy state S into the second uncertainty state SF between the static occupancy state S and the free-space state F, a state transition probability $p_{D \rightarrow D}$ 308 from the dynamic occupancy state D into the dynamic occupancy state D, a state transition probability $p_{D \rightarrow SD}$ 310 from the dynamic occupancy state D into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D, a state transition probability $p_{D \rightarrow DF}$ 312 from the dynamic occupancy state D into the third uncertainty state DF between the dynamic occupancy state D and the free-space state F, a state transition probability $p_{F \rightarrow F}$ 314 from the free-space state F into the free-space state F, a state transition probability $p_{F \rightarrow SF}$ 316 from the free-space state F into the second uncertainty state SF between the static occupancy state S and the free-space state F, a state transition probability $p_{F \rightarrow DF}$ 318 from the free-space state F into the third uncertainty state DF between the dynamic occupancy state D and the free-space state F, a state transition probability $p_{SD \rightarrow SD}$ 320 from the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D, a state transition probability $p_{SD \rightarrow SDF}$ 322 from the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D into the unknown occupancy state SDF, a state transition probability $p_{SF \rightarrow SF}$ 324 from the second uncertainty state SF between the static occupancy state S and the free-space state F into the second uncertainty state SF between the static occupancy state S and the free-space state F, a state transition probability $p_{SF \rightarrow SDF}$ 326 from the second uncertainty state SF between the static occupancy state S and the free-space state F into the unknown occupancy state SDF, a state transition probability $p_{DF \rightarrow DF}$ 328 from the third uncertainty state DF between the dynamic occupancy state D and the free-space state F into third uncertainty state DF between the dynamic occupancy state D and the free-space state F, a state transition probability $p_{DF \rightarrow SDF}$ 330 from the third uncertainty state DF between the dynamic occupancy state D and the free-space state F into the unknown occupancy state SDF and a state transition probability $p_{SDF \rightarrow SDF}$ 332 from the unknown occupancy state SDF into the unknown occupancy state SDF, wherein the state transition probability $p_{SDF \rightarrow SDF}$ 332 is equal to 1. All other entries are zero, i.e. the state transition probability is zero, so there is no state transition probability between the corresponding states.

[0068] For all of the described state transition probabilities which may be different from zero, the following conditions are met:

$$\sum_{i \in \Omega} p_{S \rightarrow i} = 1, \sum_{i \in \Omega} p_{D \rightarrow i} = 1, \sum_{i \in \Omega} p_{F \rightarrow i} = 1$$

$$\sum_{i \in \Omega} p_{SD \rightarrow i} = 1, \sum_{i \in \Omega} p_{SF \rightarrow i} = 1, \sum_{i \in \Omega} p_{DF \rightarrow i} = 1$$

[0069] If these conditions are met, then it can be shown that after an infinite number of steps without measurement update, the unknown occupancy state SDF will be reached, which is a desired behavior. In other words, after an infinite number of iterations (number of iterations $n \rightarrow \infty$) in which only the transition matrix P is applied without measurement update, all state transition probabilities concentrate in the unknown occupancy state SDF. In yet other words, in the "infinite power" of the transition matrix P, the state transition probabilities from any occupancy state to the unknown occupancy state SDF is 1 and all other state transition probabilities are set to 0:

$$\lim_{n \rightarrow \infty} P^n = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix}$$

[0070] The transition matrix P may be dependent of an estimated velocity v of an object in the area ($P = P(v)$) if it is calculated. Such parametrization may provide a better occupancy state prediction of the area.

[0071] Radar sensors and LIDAR sensors may have different characteristics of possible information available for detection, which may lead to different observation sets for radar sensors and LIDAR sensors. The set of observations for a radar sensor may be defined as $O_{\text{radar}} = \{S, D, SD, F\}$ and the set of observations for a LIDAR sensor may be defined as $O_{\text{LIDAR}} = \{SD, F\}$, wherein the abbreviations have the same meaning as described herein, i.e. a static occupancy state S, a dynamic occupancy state D, a free-space state F and a first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D.

[0072] This may mean that based on LIDAR sensors only an uncertainty information between a static occupancy and a dynamic occupancy or a free-space information (in ray-casting mode) may be deduced, without a discrimination between a static occupancy state S and a dynamic occupancy state D. Ray-casting mode may be an inverse sensor model calibration, which may model not only an area of occupancy, but also a free-space between the areas of occupancy. In this mode free-space is modelled in cells under ray between sensor origin and detection. The inverse sensor model enables to estimate occupied and empty regions, given sensor measurements. Based on radar sensors detection, information about a static occupancy information and a dynamic occupancy information may be extracted, if detection can be classified as dynamic or static. Otherwise only an uncertainty information between a static occupancy and a dynamic occupancy or a free-space information (in ray-casting mode) may be obtained from detection. For the method described herein, there may not be used a pre-filtering of the sensor information; in other words: the method described herein may work even without pre-filtering of the sensor information.

[0073] For each sensor, i.e. for radar sensors and for LIDAR sensors, an observation matrix Q_{radar} and an observation matrix Q_{LIDAR} may be defined. The observation emission probability q added to each entry of the observation matrix Q_{radar} may be dependent on a distance r from detection to the radar sensor, same as "classic" inverse sensor model (ISM), and a detection range rate \dot{r} . Based on this values, a discrimination between a static occupancy state S and a dynamic occupancy state D can be done:

$$Q_{\text{radar}}(\dot{r}, r) = \begin{bmatrix} q_{S \rightarrow S} & q_{D \rightarrow S} & q_{SD \rightarrow S} & q_{F \rightarrow S} \\ q_{S \rightarrow D} & q_{D \rightarrow D} & q_{SD \rightarrow D} & q_{F \rightarrow D} \\ q_{S \rightarrow F} & q_{D \rightarrow F} & q_{SD \rightarrow F} & q_{F \rightarrow F} \\ q_{S \rightarrow SD} & q_{D \rightarrow SD} & q_{SD \rightarrow SD} & q_{F \rightarrow SD} \\ q_{S \rightarrow SF} & q_{D \rightarrow SF} & q_{SD \rightarrow SF} & q_{F \rightarrow SF} \\ q_{S \rightarrow DF} & q_{D \rightarrow DF} & q_{SD \rightarrow DF} & q_{F \rightarrow DF} \\ q_{S \rightarrow SDF} & q_{D \rightarrow SDF} & q_{SD \rightarrow SDF} & q_{F \rightarrow SDF} \end{bmatrix}$$

[0074] The observation matrix Q_{LIDAR} may be dependent on the distance r from the LIDAR sensor:

$$Q_{\text{LIDAR}}(r) = \begin{bmatrix} q_{SD \rightarrow S} & q_{F \rightarrow S} \\ q_{SD \rightarrow D} & q_{F \rightarrow D} \\ q_{SD \rightarrow F} & q_{F \rightarrow F} \\ q_{SD \rightarrow SD} & q_{F \rightarrow SD} \\ q_{SD \rightarrow SF} & q_{F \rightarrow SF} \\ q_{SD \rightarrow DF} & q_{F \rightarrow DF} \\ q_{SD \rightarrow SDF} & q_{F \rightarrow SDF} \end{bmatrix}$$

[0075] Fig. 4 shows a flow diagram 400 illustrating a method for occupancy state detection according to various embodiments. At 402, a probability distribution over a list of possible occupancy states of the area at a previous point in time may be determined. At 404, measurement data related to the area at the pre-determined point in time may be determined. At 406, a probability distribution over the list of possible occupancy states of the area at the pre-determined point in time may be determined, based on the measurement data and the probability distribution over the list of possible occupancy states of the area at the previous point in time wherein the list of possible occupancy states comprises: a static occupancy state S, a dynamic occupancy state D, a free-space state F, a first uncertainty state SD between the

static occupancy state S and the dynamic occupancy state D, a second uncertainty state SF between the static occupancy state S and the free-space state F, a third uncertainty state DF between the dynamic occupancy state D and the free-space state F, and an unknown occupancy state SDF.

5 **[0076]** According to various embodiments, the probability distribution over the list of possible occupancy states of the area at the previous point in time comprises a pre-determined initial state distribution over the list of possible occupancy states of the area.

[0077] According to various embodiments, the initial state distribution over the list of possible occupancy states of the area comprises an equal distribution over the list of possible occupancy states of the area.

10 **[0078]** According to various embodiments, the probability distribution over the list of possible occupancy states of the area at the previous point in time is determined based on measurement data related to the area at the previous point in time and a probability distribution over the list of possible occupancy states of the area at a further point in time preceding the previous point in time.

15 **[0079]** According to various embodiments, the probability distribution over the list of possible occupancy states of the area at the pre-determined point in time is determined further based on a transition matrix comprising a plurality of state transition probabilities between possibly occupancy states.

20 **[0080]** According to various embodiments, the following state transition probabilities are different from zero: a state transition probability 302 from the static occupancy state S into the static occupancy state S; a state transition probability 304 from the static occupancy state S into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D; a state transition probability 306 from the static occupancy state S into the second uncertainty state SF between the static occupancy state S and the free-space state F; a state transition probability 308 from the dynamic occupancy state D into the dynamic occupancy state D; a state transition probability 310 from the dynamic occupancy state D into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D; a state transition probability 312 from the dynamic occupancy state D into the third uncertainty state DF between the dynamic occupancy state D and the free-space state F; a state transition probability 314 from the free-space state F into the free-space state F; a state transition probability 316 from the free-space state F into the second uncertainty state SF between the static occupancy state S and the free-space state F; a state transition probability 318 from the free-space state F into the third uncertainty state DF between the dynamic occupancy state D and the free-space state F; a state transition probability 320 from the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D into the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D; a state transition probability 322 from the first uncertainty state SD between the static occupancy state S and the dynamic occupancy state D into the unknown occupancy state SDF; a state transition probability 324 from the second uncertainty state SF between the static occupancy state S and the free-space state F into the second uncertainty state SF between the static occupancy state S and the free-space state F; a state transition probability 326 from the second uncertainty state SF between the static occupancy state S and the free-space state F into the unknown occupancy state SDF; a state transition probability 328 from the third uncertainty state DF between the dynamic occupancy state D and the free-space state F into third uncertainty state DF between the dynamic occupancy state D and the free-space state F; a state transition probability 330 from the third uncertainty state DF between the dynamic occupancy state D and the free-space state F into the unknown occupancy state SDF; a state transition probability 332 from the unknown occupancy state SDF into the unknown occupancy state SDF is equal to 1.

35 **[0081]** According to various embodiments, the transition matrix is dependent of an estimated velocity of an object in the area.

40 **[0082]** According to various embodiments, the probability distribution over the list of possible occupancy states of the area at the pre-determined point in time is determined further based on an observation matrix comprising observation emission probabilities.

45 **[0083]** According to various embodiments, the area comprises a cell of an occupancy grid, the occupancy grid comprising a plurality of further cells.

[0084] According to various embodiments, the measurement data is determined based on a LIDAR sensor and the measurement data comprises an uncertainty information between a static occupancy and a dynamic occupancy or a free-space information.

50 **[0085]** According to various embodiments, the measurement data is determined based on a radar sensor and the measurement data comprises a static occupancy information, a dynamic occupancy information, an uncertainty information between a static occupancy and a dynamic occupancy, or a free-space information.

[0086] According to various embodiments, the observation matrix is dependent on at least one of a detection range rate from the radar sensor and a distance from the radar sensor.

55 **[0087]** Each of the steps 402, 404, 406 and the further steps described above may be performed by computer hardware components.

[0088] With the methods and systems as described herein, occupancy state detection may be provided.

[0089] Fig. 5 shows a computer system 500 with a plurality of computer hardware components configured to carry out

steps of a computer implemented method for occupancy state detection according to various embodiments. The computer system 500 may include a processor 502, a memory 504, and a non-transitory data storage 506. A camera 508 and/or a distance sensor 510 (for example a radar sensor or a LIDAR sensor) may be provided as part of the computer system 500 (like illustrated in Fig. 5), or may be provided external to the computer system 500.

5 **[0090]** The processor 502 may carry out instructions provided in the memory 504. The non-transitory data storage 506 may store a computer program, including the instructions that may be transferred to the memory 504 and then executed by the processor 502. The camera 508 and/or the distance sensor 510 may be used to determine measurement data, for example measurement data related to the area at the pre-determined point in time as described herein.

10 **[0091]** The processor 502, the memory 504, and the non-transitory data storage 506 may be coupled with each other, e.g. via an electrical connection 512, such as e.g. a cable or a computer bus or via any other suitable electrical connection to exchange electrical signals. The camera 508 and/or the distance sensor 510 may be coupled to the computer system 500, for example via an external interface, or may be provided as parts of the computer system (in other words: internal to the computer system, for example coupled via the electrical connection 512).

15 **[0092]** The terms "coupling" or "connection" are intended to include a direct "coupling" (for example via a physical link) or direct "connection" as well as an indirect "coupling" or indirect "connection" (for example via a logical link), respectively.

[0093] It will be understood that what has been described for one of the methods above may analogously hold true for the computer system 500.

Reference numeral list

20 **[0094]**

| | |
|--------|--|
| 100 | Markov Chain |
| 102 | occupancy state h_1 |
| 25 104 | occupancy state h_2 |
| 106 | occupancy state h_3 |
| 108 | occupancy state h_4 |
| 110 | measurement m_1 |
| 112 | measurement m_2 |
| 30 114 | measurement m_3 |
| 116 | measurement m_4 |
| 118 | arrow |
| 120 | arrow |
| 122 | arrow |
| 35 124 | arrow |
| 126 | arrow |
| 128 | arrow |
| 130 | arrow |
| 132 | arrow |
| 40 200 | single probability distribution calculation |
| 202 | probability distribution at a pre-determined point in time |
| 204 | probability distribution at a previous point in time |
| 206 | probability distribution at a previous point in time |
| 45 208 | probability distribution at a previous point in time |
| 210 | probability distribution at a previous point in time |
| 212 | observation at a pre-determined point in time |
| 214 | state transition probability |
| 216 | state transition probability |
| 50 218 | state transition probability |
| 220 | state transition probability |
| 222 | observation emission probability |
| 300 | state transition graph |
| 55 S | static occupancy state |
| D | dynamic occupancy state |
| F | free-space state |
| SD | first uncertainty state |

| | | |
|----|-----|---|
| | SF | second uncertainty state |
| | DF | third uncertainty state |
| | SDF | unknown occupancy state |
| | 302 | state transition probability |
| 5 | 304 | state transition probability |
| | 306 | state transition probability |
| | 308 | state transition probability |
| | 310 | state transition probability |
| | 312 | state transition probability |
| 10 | 314 | state transition probability |
| | 316 | state transition probability |
| | 318 | state transition probability |
| | 320 | state transition probability |
| | 322 | state transition probability |
| 15 | 324 | state transition probability |
| | 326 | state transition probability |
| | 328 | state transition probability |
| | 330 | state transition probability |
| | 332 | state transition probability |
| 20 | 400 | flow diagram illustrating a method for occupancy state detection according to various embodiments |
| | 402 | step of determining a probability distribution at a previous point in time |
| | 404 | step of determining measurement data |
| | 406 | step of determining a probability distribution at a pre-determined point in time |
| 25 | 500 | computer system according to various embodiments |
| | 502 | processor |
| | 504 | memory |
| | 506 | non-transitory data storage |
| | 508 | camera |
| 30 | 510 | distance sensor |
| | 512 | connection |

Claims

- 35
1. Computer implemented method for occupancy state detection in an area for a pre-determined point in time, the method comprising the following steps carried out by computer hardware components:
- 40
- determining a probability distribution (204, 206, 208, 210) over a list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at a previous point in time;
 - determining measurement data related to the area at the pre-determined point in time; and
 - determining a probability distribution (202) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the pre-determined point in time based on the measurement data and the probability distribution (204, 206, 208, 210) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the previous point in time;
- 45
- wherein the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) comprises: a static occupancy state (S), a dynamic occupancy state (D), a free-space state (F), a first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D), a second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F), a third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F), and an unknown occupancy state (SDF).
- 50
2. The method of claim 1,
- 55
- wherein the probability distribution (204, 206, 208, 210) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the previous point in time comprises a pre-determined initial state distribution over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area.
3. The method of claim 2,

wherein the initial state distribution over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area comprises an equal distribution over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area.

4. The method of at least one of claims 1 to 3,
 5 wherein the probability distribution (204, 206, 208, 210) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the previous point in time is determined based on measurement data related to the area at the previous point in time and a probability distribution over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at a further point in time preceding the previous point in time.
- 10 5. The method of at least one of claims 1 to 4,
 wherein the probability distribution (202) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the pre-determined point in time is determined further based on a transition matrix comprising a plurality of state transition probabilities (302, 304, 306, 308, 310, 312, 314, 316, 318, 320, 322, 324, 326, 328, 330, 332) between possibly occupancy states (S, D, F, SD, SF, DF, SDF).
- 15 6. The method of claim 5,
 wherein the following state transition probabilities (302, 304, 306, 308, 310, 312, 314, 316, 318, 320, 322, 324, 326, 328, 330, 332) are different from zero:
- 20 - a state transition probability (302) from the static occupancy state (S) into the static occupancy state (S);
 - a state transition probability (304) from the static occupancy state (S) into the first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D);
 - a state transition probability (306) from the static occupancy state (S) into the second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F);
 25 - a state transition probability (308) from the dynamic occupancy state (D) into the dynamic occupancy state (D);
 - a state transition probability (310) from the dynamic occupancy state (D) into the first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D);
 - a state transition probability (312) from the dynamic occupancy state (D) into the third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F);
 30 - a state transition probability (314) from the free-space state (F) into the free-space state (F);
 - a state transition probability (316) from the free-space state (F) into the second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F);
 - a state transition probability (318) from the free-space state (F) into the third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F);
 35 - a state transition probability (320) from the first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D) into the first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D);
 - a state transition probability (322) from the first uncertainty state (SD) between the static occupancy state (S) and the dynamic occupancy state (D) into the unknown occupancy state (SDF);
 40 - a state transition probability (324) from the second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F) into the second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F);
 - a state transition probability (326) from the second uncertainty state (SF) between the static occupancy state (S) and the free-space state (F) into the unknown occupancy state (SDF);
 45 - a state transition probability (328) from the third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F) into third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F);
 - a state transition probability (330) from the third uncertainty state (DF) between the dynamic occupancy state (D) and the free-space state (F) into the unknown occupancy state (SDF);
 50 - a state transition probability (332) from the unknown occupancy state (SDF) into the unknown occupancy state (SDF) is equal to 1.
7. The method of at least one of claims 5 to 6,
 wherein the transition matrix is dependent of an estimated velocity of an object in the area.
- 55 8. The method of at least one of claims 1 to 7,
 wherein the probability distribution (202) over the list of possible occupancy states (S, D, F, SD, SF, DF, SDF) of the area at the pre-determined point in time is determined further based on an observation matrix comprising

observation emission probabilities (222).

5 9. The method of at least one of claims 1 to 8,
wherein the area comprises a cell of an occupancy grid, the occupancy grid comprising a plurality of further cells.

10 10. The method of claim 1 to 9,
wherein the measurement data is determined based on a LIDAR sensor and the measurement data comprises an
uncertainty information between a static occupancy and a dynamic occupancy or a free-space information.

15 11. The method of at least one of claims 1 to 10,
wherein the measurement data is determined based on a radar sensor and the measurement data comprises a
static occupancy information, a dynamic occupancy information, an uncertainty information between a static occu-
pancy and a dynamic occupancy, or a free-space information.

20 12. The method of claims 11,
wherein the observation matrix is dependent on at least one of a detection range rate from the radar sensor and a
distance from the radar sensor.

25 13. Computer system (500), the computer system (500) comprising a plurality of computer hardware components con-
figured to carry out steps of the computer implemented method of at least one of claims 1 to 12.

30 14. Vehicle, comprising the computer system (500) of claim 13 and a sensor,
wherein the measurement data is determined based on an output of the sensor.

35 15. Non-transitory computer readable medium comprising instructions for carrying out the computer implemented meth-
od of at least one of claims 1 to 12.

40

45

50

55

60

65




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5



EUROPEAN SEARCH REPORT

Application Number
EP 21 17 6539

5

10

15

20

25

30

35

40

45

50

55

| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|---|--|---|--|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (IPC) |
| X | ERKENT OZGUR ET AL: "Semantic Grid Estimation with a Hybrid Bayesian and Deep Neural Network Approach", 2018 IEEE/RSJ INTERNATIONAL CONFERENCE ON INTELLIGENT ROBOTS AND SYSTEMS (IROS), IEEE, 1 October 2018 (2018-10-01), pages 888-895, XP033490778, DOI: 10.1109/IROS.2018.8593434 [retrieved on 2018-12-27] | 1,13-15 | INV. G01S13/931 G01S17/931 G06K9/00 |
| A | * chapter "B. Bayesian Occupancy Grids" * ----- | 2-12 | |
| A | RAPP MATTHIAS ET AL: "Hidden Markov model-based occupancy grid maps of dynamic environments", 2016 19TH INTERNATIONAL CONFERENCE ON INFORMATION FUSION (FUSION), ISIF, 5 July 2016 (2016-07-05), pages 1780-1788, XP032935222, [retrieved on 2016-08-01] * chapters IV.A and V.B; figure 5 * ----- | 1-15 | |
| The present search report has been drawn up for all claims | | | TECHNICAL FIELDS SEARCHED (IPC) |
| | | | G01S G06K |
| Place of search | | Date of completion of the search | Examiner |
| Munich | | 12 November 2021 | Damp, Stephan |
| CATEGORY OF CITED DOCUMENTS | | | |
| X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document | | T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document | |

1
EPO FORM 1503 03 82 (P04C01)